



**A** Effective top tube (mm)

**B** Dimensione (mm)

**C** Effective seat tube angle (°)

**D** Head tube angle (°)

**E** Chainstay (mm)

**F** Fork offset (mm)

**H** Wheelbase (mm)

**J** Fork length (mm)

**K** bottom bracket drop (mm)

**L** Front center distance (mm)

**M** Head tube length (mm)

**O** Reach (mm)

	A	B	C	D	E	F	H	J	K	L	M	O
<b>48</b>	510	480	74.5	71.5	401	50	963	365	66	571	83	128
<b>49</b>	515	490	74.5	71.5	402	50	968	365	69	576	90	131
<b>50</b>	520	500	74.5	72.5	402	50	965	365	70	573	95	134
<b>51</b>	525	510	74.0	72.5	402	50	964	365	73	573	101	141
<b>52</b>	535	520	74.0	72.5	403	50	975	365	73	583	111	143
<b>53</b>	540	530	74.0	73.0	405	45	973	365	73	579	117	146
<b>54</b>	545	540	73.5	73.0	405	45	973	365	73	579	126	153
<b>55</b>	550	550	73.5	73.0	405	45	978	365	73	584	136	156
<b>56</b>	560	560	73.5	73.0	405	45	988	365	73	594	146	159
<b>57</b>	565	570	73.5	73.0	406	45	994	365	73	599	156	162
<b>58</b>	570	580	73.0	73.0	407	45	995	365	73	599	165	170
<b>59</b>	575	590	73.0	73.0	408	45	1001	365	73	604	175	173
<b>60</b>	580	600	73.0	73.0	409	45	1007	365	73	609	185	175
<b>61</b>	580	610	73.0	73.0	409	45	1007	365	73	609	195	178
<b>62</b>	590	620	73.0	73.0	409	45	1017	365	73	619	205	181
<b>63</b>	590	630	73.0	73.0	410	45	1018	365	73	619	215	184
<b>64</b>	595	640	73.5	74.0	410	45	1019	365	73	619	222	182